

MODEL	Fi VARIANT	i3S VARIANT	
ENGINE			
Engine Type	Air Cooled, 4-Stroke Single Cylinder OHC		
Displacement	124.6cc		
Max Power	6.8 kW (9.1 BHP) @ 7000	6.5 kW (8.7 BHP) @ 6750	
	Revolutions Per Minute (rpm	Revolutions Per Minute (rpm)	
Max Torque	10.2 Nm @ 5000 R	evolutions Per Minute (rpm)	
Fuel System	Fuel Injection	Carburetor	
Starting	Self-Start / Kick-Start		
lgnition	Electronic Control Unit (ECL	Digital TCI Ignition System (TCI)	
TRANSMISSION			
Clutch	Dry, Centrifugal		
Gear Box	Variomatic Drive		
SUSPENSION			
Front	Telescopic Fork		
Rear	Single Coil Spring Hydraulic Type		
BRAKES			
Front Brake Type	Disc Brake 190 mi	m Drum Brake 130 mm / Disc Brake 190 mm	
Rear Brake Type	Drum Brake 130 mm		
TYRES			
Front Tyre	90/90-12		
Rear Tyre	90/100-10		
ELECTRICALS			
Battery (V-Ah)	12V-4Ah	ETZ-5 MF-Battery	
DIMENSIONS			
Length x Width x Height	1843 mm X 718 mm X 1188 mm		
Wheelbase	1261 mm		
Seat Height	775 mm		
Ground Clearance	155 mm		
WEIGHT			
Kerb Weight	110 kg	Drum: 109 kg / Disc 110 kg	
Maximum Payload		130 kg	
Fuel Tank Capacity	5.0 L	5.5 L	
OPTIONAL ACCESSORI	FS		

FEATURES





COLOURS



Matte Vernier Grey



Pearl Fadeless White

Regd. Office: Hero MotoCorp Ltd. 34, Community Centre, Basant Lok, Vasant Vihar, New Dethi - 110057, India. CIN: L35911DL1984PLC017354.



Authorized Outlet

Matte Red

It is our endeavour to constantly improve our product. This could lead to changes in product specifications without notice. Accessories and features shown may not be part of the standard fitment. Always wear a helmet while riding a two-wheeler. For further information, contact nearest Hero MotoCorp's authorized outlet(s) or call Toll Free No.: 1800-266-0018 or visit website www.heromotocorp.com.